


SOLAR'S MOST TRUSTED



REC ALPHA[®] PURE-RX SERIES

DATASHEET



9 A MODULE CURRENT
COMPATIBLE WITH MLPE

450 - 470W
HETEROJUNCTION
TECHNOLOGY

226 W/M² POWER DENSITY

>92% POWER IN YEAR 25

-0.24%/°C TEMPERATURE
COEFFICIENT OF P_{MAX}




ELIGIBLE

REC ALPHA® PURE-RX SERIES DATASHEET



GENERAL DATA

Cell Type	88 half-cut bifacial REC heterojunction cells, with gapless technology
Glass	3.2 mm solar glass with anti-reflective surface treatment in accordance with EN12150
Backsheet	Highly resistant polymer (Black)
Frame	Anodized aluminum (Black)
Junction Box	4-part, 4 bypass diodes, IP68 rated, in accordance with IEC 62790:2020
Connectors	Stäubli MC4 PV-KBT4/KST4 (4 mm ²) in accordance with IEC 62852:2014, IP68 only when connected
Cable	4 mm ² solar cable, 1.70 m + 1.70 m in accordance with EN50618:2014
Dimensions	1728 x 1205 x 30 mm (2.08 m ²)
Weight	22.7 kg
Origin	Made in Singapore



Specifications subject to change without notice.

ELECTRICAL DATA

PRODUCT CODE*: RECXXXAA PURE-RX

Power Output - P _{MAX} (WP)	450	460	470
Watt Class Sorting - (W)	0/+10	0/+10	0/+10
Nominal Power Voltage - V _{MPP} (V)	54.3	54.9	55.4
Nominal Power Current - I _{MPP} (A)	8.29	8.38	8.49
Open Circuit Voltage - V _{OC} (V)	65.6	65.8	65.9
Short Circuit Current - I _{SC} (A)	8.81	8.88	8.95
Power Density (W/m ²)	216	221	226
Panel Efficiency (%)	21.6	22.1	22.6

CERTIFICATIONS

- ISO 14001; ISO 9001; IEC 45001; IEC 62941
- IEC 61215:2021; IEC 61730:2023; UL 61730
- ISO 11925-2 Ignitability (EN 13501-1 Class E)
- IEC 62716 Ammonia Resistance
- IEC 61701 Salt Mist (SM6)
- IEC 61215:2016 Hailstone (35 mm)
- UL 61730 Fire Type 2



MODULE RATINGS

Module Operating Temperature [T98] [§]	70°C
Min. Environmental Temperature	-40°C
System Voltage	1000 V
Maximum Test Load (4 Point Mounting, Front)*	+7000 Pa (714 Kg/m ²)
Maximum Test Load (4 Point Mounting, Rear)**	-4000 Pa (408 Kg/m ²)
Maximum Test Load (6 Point Mounting, Front)**	+8000 Pa (816 Kg/m ²)
Maximum Test Load (6 Point Mounting, Rear)**	-6000 Pa (612 Kg/m ²)
Max Series Fuse Rating	25 A
Max Reverse Current	25 A

TEMPERATURE RATINGS*

Nominal Module Operating Temperature	44 ± 2°C
Temperature coefficient of P _{MAX}	-0.24%/°C
Temperature coefficient of V _{OC}	-0.24%/°C
Temperature coefficient of I _{SC}	0.04%/°C

*The temperature coefficients stated are linear values


Design load = Test load / 1.5 (safety factor)

[§] 98th percentile operating temperature

* IEC 61730/UL 61730 certified. Refer to installation manual.

** Internal testing. Refer to installation manual.

Available from:



Founded in 1996, REC Group is an international pioneering solar energy company dedicated to empowering consumers with clean, affordable solar power. As Solar's Most Trusted, REC is committed to high quality, innovation, and a low carbon footprint in the solar materials and solar panels it manufactures. Headquartered in Norway with operational headquarters in Singapore, REC also has regional hubs in North America, Europe, and Asia-Pacific.

WARRANTY

	Standard	REC ProTrust	
Installed by an REC Certified Professional	No	Yes	Yes
System Size	All	<25 kW	25-500 kW
Product Warranty (yrs)	20	25	25
Power Warranty (yrs)	25	25	25
Labor Warranty (yrs)	0	25	10
Power in Year 1	98%	98%	98%
Annual Degradation	0.25%	0.25%	0.25%
Power in Year 25	92%	92%	92%


REC ProTrust Warranty applies only for i) REC panels installed by an REC Certified Solar Professional, and ii) panels have been registered by the installer with REC. Subject to System Size and further conditions. See www.recgroup.com for details.

DELIVERY INFORMATION

Panels per Pallet	33
Panels per 40 ft GP/high cube container	594 (18 Pallets)
Panels per 13.6 m truck	660 (20 Pallets)

LOW LIGHT BEHAVIOUR

Typical low irradiance performance of module at STC:



REC Solar PTE. LTD.
20 Tuas South Ave. 14
Singapore 637312
post@recgroup.com
www.recgroup.com



REF: PW-DS-12-06-REV-4.3/B/IEC EN 12.2024